

The **Casing Packer** is a large bore, single grip packer used to isolate damaged casing and for production or injection. This packer can be run in tension or compression and can be used as a liner hanger when equipped with a right-hand release sub. Coarse deep whickered slips allow this packer set in open hole or scaly casing. For open-hole set, this packer can be equipped with two elongated packing elements to assure a positive seal.

Features and Benefits

- Set / Run in tension or compression
- Applicable for set in open hole
- Can be used as a liner hanger
- Full opening
- Coarse, deep whickered slip teeth
- Available with right-hand or left-hand set, manual or automatic release

Specifications					
Casing			Tool O.D.	Tool ID	Thread Connection Box Up / Pin Down
Size	Weight	Recommended Hole Size			
in mm	lb/ft kg/m	in mm	in mm	in mm	in mm
4-1/2 114.3	9.5 - 13.5 14.1 - 20.1	3.920 - 4.090 99.6 - 103.9	3.750 95.3	2.50 63.5	2-7/8 EUE 73.0 EUE
	15.1 22.5	3.826 97.2	3.656 92.9		
5-1/2 139.7	13.0 - 17.0 19.3 - 25.3	4.892 - 5.044 124.3 - 128.1	4.650 118.1	3.50 88.9	4 NUE 101.6 NUE
	13.0 - 20.0 19.3 - 29.8	4.778 - 5.044 121.4 - 128.1	4.625 117.5	3.00 76.2	3-1/2 EUE 88.9 EUE
7 177.8	17.0 - 26.0 25.3 - 38.7	6.276 - 6.538 159.4 - 166.1	6.000 152.4	4.75 120.65	5-1/2 LTC 139.7 LTC
	17.0 - 38.0 25.3 - 56.6	5.920 - 6.538 150.4 - 166.1	5.750 146.1	4.00 101.60	4-1/2 LTC 114.3 LTC
	20.0 - 29.0 29.8 - 43.2	6.184 - 6.456 157.1 - 164.0	5.969 151.6	4.50 114.3	5 LTC 127.0 LTC

