

# Permapak Packer – Single Bore



The **Permapak Seal Bore Packer** can be used for single or multiple zone completions. It is designed for wells where high pressure/temperatures and corrosive fluids are present, and it is available in a variety of elastomers and seal bore materials to meet a wide range of hostile downhole environments. This packer is recommended for injection stimulation and testing or can become a temporary bridge plug when used with a knock-out or pump-out bottom assembly. The Permapak Seal Bore Packer comes with a complete line of tubing seal accessories and elastomers.

## Features and Benefits

- Electric line, hydraulic or mechanical set
- Components keyed for milling
- Anti-extrusion rings expand to casing ID to prevent rubber extrusion
- Full circle slips allow for faster run time

Specifications					
Casing		Recommended Hole Size	Tool OD	Seal Bore	Min. ID Thru Seals
Size	Weight			Upper	
in mm	lb/ft kg/m	in mm	in mm	in mm	in mm
4-1/2 114.3	9.5 - 13.5 14.1 - 20.1	3.920 - 4.090 99.6 - 103.9	3.750 95.25	2.500 63.50	1.910 48.51
				2.688 68.28	1.938 49.23
	15.1 22.5	3.826 97.2	3.600 91.44	2.500 63.50	1.910 48.51
5-1/2 139.7	13.0 - 17.0 19.3 - 25.3	4.892 - 5.044 124.3 - 128.1	4.532 115.11	2.688 68.28	1.938 49.23
				3.000 76.20	2.375 60.33
	17.0 - 23.0 25.3 - 34.2	4.670 - 4.892 118.6 - 124.3	4.438 112.73	2.688 68.28	1.938 49.23
				3.000 76.20	2.375 60.33
	23.0 - 26.0 34.2 - 38.7	4.548 - 4.670 115.5 - 118.6	4.250 107.95	2.688 68.28	1.938 49.23
				3.250 82.55	2.416 61.37
7 177.8	17.0 - 23.0 25.3 - 34.2	6.366 - 6.538 161.7 - 166.1	6.000 152.40	4.000 101.60	3.000 76.20
				3.250 82.55	2.416 61.37
	23.0 - 32.0 34.2 - 47.6	6.094 - 6.366 154.8 - 161.7	5.813 147.65	4.000 101.60	3.000 76.20
				3.250 82.55	2.416 61.37
	32.0 - 38.0 47.6 - 56.6	5.920 - 6.094 150.4 - 154.8	5.625 142.88	4.000 101.60	3.000 76.20
				3.250 82.55	2.416 61.37

