

# Snapset II Packer



The **Snapset II Packer** is a compression set tool requiring only straight set down weight to pack-off. This packer is run above another compression set packer to selectively treat, produce or inject in multiple zone completions. This packer is also used to isolate casing hole perforations. This packer features a large by-pass area to prevent swabbing when running and retrieving. Once the packer is set, pressure from above or below acts down on the valve to maintain the seal and prevent upward movement of the tubing. When releasing, the valve allows debris to be washed from the upper slips. This packer is equipped with an internal latch to prevent setting prematurely when running in the hole. When releasing, the latch re-engages to allow movement.

## Features and Benefits

- Large internal by-pass
- Set down to pack off, pick up to release
- Mechanical slips vs. hydraulic buttons
- Differential pressure holds valve closed

Specifications					
Casing			Tool		Thread Connection Box Up / Pin Down
Size	Weight	Recommended Hole Size	O.D.	I.D.	
in mm	lb/ft kg/m	in mm	in mm	in mm	in mm
4-1/2 114.3	9.5 - 13.5 14.1 - 20.1	3.920 - 4.090 99.6 - 103.9	3.750 95.3	1.94 49.3	2-3/8 EUE 60.3 EUE
	15.1 22.5	3.826 97.2	3.656 92.9		
	18.8 28.0	3.640 92.5	3.437 87.3	1.500 38.1	1.90 EUE 48.3 EUE
5-1/2 139.7	14.0 - 20.0 20.8 - 29.8	4.778 - 5.012 121.4 - 127.3	4.625 117.5	2.000 50.8	2-3/8 EUE 60.3 EUE
				2.38 60.5	2-7/8 EUE 73.0 EUE
	20.0 - 23.0 29.8 - 34.2	4.670 - 4.778 118.6 - 121.4	4.500 114.3	2.000 50.8	2-3/8 EUE 60.3 EUE
				2.38 60.5	2-7/8 EUE 73.0 EUE
7 177.8	17.0 - 26.0 25.3 - 38.7	6.276 - 6.538 159.4 - 166.1	6.000 152.4	2.50 63.5	2-7/8 EUE 73.0 EUE
				3.00 76.2	3-1/2 EUE 88.9 EUE
	26.0 - 32.0 38.7 - 47.6	6.094 - 6.276 154.8 - 159.4	5.875 149.2	2.50 63.5	2-7/8 EUE 73.0 EUE

